



CORE 3


ROUND, CUTOUT, DIRECT/INDIRECT ILLUMINATION



SPECIFICATIONS

PROFILE	Round
SIZES	3.5" diameter
LED OUTPUT	500lm - 1,500lm
CCT/CRI	2700K/3000K/3500K/4000K • 90CRI or BIOS
DIMMING/DRIVER	Canopy and Remote Driver: 0-10V, Phase, DALI, DMX, eldoLED, Lutron®, PoE (Molex, Igor, NuLEDs). Dimming to 0% for select models
POWER	6.8W to 50.4W per fixture
INPUT	100VAC to 277VAC Phase dimmable versions are 120VAC only
OPTICS	15° - 80° distribution spun aluminum reflectors. Field replaceable without tools.
FINISHES	Powder coat - TGIC polyester
MATERIAL	Extruded aluminum with galvanized steel hardware
ENVIRONMENT	Indoor dry or damp locations


DISTRIBUTIONS & PROFILES



Available in any combination of distributions for direct and indirect.



CORE 3 DIRECT/INDIRECT PENDANT

CORE 3 DIRECT/INDIRECT SCENCE



CORE 3 DIRECT/INDIRECT PENDANT

CORE 3 DIRECT/INDIRECT SCENCE



Not to scale. Dimensions are nominal. Consult factory for CAD drawing

*Safety and Performance information available on last page. Output and other specifications available on page 6.





PRODUCT SUBMITTAL QUICK WORKSHEET

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----

EXAMPLE: C¹**CT3** – **20902725HL** – **20902725HL** – **RV00** – **2C** – **DOB** – **BABK/12** – **ADA** – **NLT** – **EMB**
 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21

1. MODEL (CHOOSE 1)	2. OUTPUT - DIRECT* (CHOOSE 1)	3. CRI - DIRECT* (CHOOSE 1)	4. CCT - DIRECT* (CHOOSE 1)
CT3 Pendant	05 ² 500lm	90 90	27 2700K
CCU3 Sconce	10 1000lm	BD ³ BIOS Dynamic	30 3000K
	15 1500lm	⁴ Dynamic BIOS SkyBlue® 490nm LED can be tuned out with most LED driver and dimmer combinations. See pages 7-8 for details.	35 3500K
	⁵ See BOIS Dynamic supplement on pages 7-8 for BIOS lamping options.		40 4000K
	⁶ Available for V01 dimming only.		⁷ Not available in BIOS Dynamic.

5. REFLECTOR - DIRECT* (CHOOSE 1)	6. OPTICAL ACCESSORY - DIRECT (CHOOSE 1)	7. OUTPUT - INDIRECT* (CHOOSE 1)	8. CRI - INDIRECT* (CHOOSE 1)
15 15° (0.3 S/MH)	NN None	05 ² 500lm	90 90
25 25° (0.4 S/MH)	HL Honeycomb Louver	10 1000lm	BD ³ BIOS Dynamic
35 35° (0.6 S/MH)	DF Diffusion Lens	15 1500lm	⁴ Dynamic BIOS SkyBlue® 490nm LED can be tuned out with most LED driver and dimmer combinations. See pages 7-8 for details.
55 55° (0.9 S/MH)	LS Linear Spread Lens (60° x 1°)	⁵ See BIOS Dynamic supplement on pages 7-8 for BIOS lamping options.	
80 80° (1.4 S/MH)	WW Wall Wash Lens (shifts beam 20° from vertical)	⁶ Phase dimming not available for 500lm	
BF ² Baffle			

¹Beam angles noted above are nominal.
²Baffles are only compatible with the NN optical accessory.

9. CCT - INDIRECT (CHOOSE 1)	10. REFLECTOR - INDIRECT* (CHOOSE 1)	11. OPTICAL ACCESSORY - INDIRECT (CHOOSE 1)	12. DRIVER LOCATION* (CHOOSE 1)
27 2700K	15 15° (0.3 S/MH)	NN None	R Remote
30 3000K	25 25° (0.4 S/MH)	HL Honeycomb Louver	D Deep Canopy
35 3500K	35 35° (0.6 S/MH)	DF Diffusion Lens	⁵ See 'Dimming/driver location compatibility on page 9 to ensure correct dimming specification.
40 4000K	55 55° (0.9 S/MH)	LS Linear Spread Lens (60° x 1°)	
	80 80° (1.4 S/MH)	WW Wall Wash Lens (shifts beam 20° from vertical)	
	BF ² Baffle		

¹Beam angles noted above are nominal.
²Baffles are only compatible with the NN optical accessory.

13. DIMMING* (CHOOSE 1)	14. NUMBER OF CIRCUITS (CHOOSE 1)	15. SHELL CUTOUT* (CHOOSE 1)	16. HEAT SINK FINISH* (CHOOSE 1)
V00 (0-10V, dim to 0%)	1C 1 Circuit	R Round	STANDARD HEAT SINK FINISHES*
V01 (0-10V, dim to 1%)	2C 2 Circuits	S Square	-- Manually type in finish code (Ex: OB = Oil-Rubbed Bronze)
P01 (ELV/TRIAC phase dim to 1%)		D Dual	SPECIAL ORDER HEAT SINK FINISHES*
ELDVO (eldoLED, 0-10V, dim to 0%)		Z ⁵ Custom	RAL---- Specify RAL Classic Color (Ex: RAL 3003) -
LDE1 (Lutron ECOSYS1, 0-10V, dim to 1%)		⁶ See page 4 for standard shell cutout options. ⁷ Consult factory for custom cutout options.	CCM---- Custom Color Match
DALI (DALI, dim to 0%)			⁸ See page 6 for finish chart.
DMX (DMX, dim to 0%)			⁹ Manually type the finish code into the parametric code above.
POEM ³ (POE Molex)			
POE1 ³ (POE IGOR)			
POEN ³ (POE Nuleds)			
POE ^{3,4} (POE Ready)			

¹See 'Driver', 'Sensor', and 'dimming/driver compatibility' charts for sensor and dimming compatibility.
²Consult factory for BIOS Dynamic dimming options.
³POE drivers only compatible with remote driver (R) location. Driver size may change depending on lumen package.
⁴Choose if desired PoE solution not listed. Contact customer service to review and confirm the PoE system of your choice.

CONTINUES ON NEXT PAGE →

SS121823



PRODUCT SUBMITTAL QUICK WORKSHEET

EXAMPLE: CCT3 – 20902725HL – 20902725HL – RV00 – 2C – DOB – BABK/12 – ADA – NLT – EMB

17. SHELL COLOR* (CHOOSE 1)	18. SUSPENSION* (CHOOSE 1)	19. SUSPENSION OPTIONS (OPTIONAL CHOOSE 1)	20. SENSOR OPTIONS* (OPTIONAL CHOOSE 1)
<p>STANDARD FINISHES</p> <p>SW <input type="checkbox"/> Satin White</p> <p>SB <input checked="" type="checkbox"/> Satin Black</p> <p>AS <input type="checkbox"/> Aluminum Silver Anodized Effect</p> <p>TB <input checked="" type="checkbox"/> Textured Black</p> <p>BA <input type="checkbox"/> Brushed Aluminum</p> <p>PREMIUM FINISHES</p> <p>-- See chart on page 6 for premium finishes. Manually type in the finish code (Ex: OB = Oil-Rubbed Bronze)</p> <p>SPECIAL ORDER FINISHES*</p> <p>RAL____ Specify RAL Classic Color (Ex: RAL 3003)</p> <p>CCM____ Custom Color Match</p>	<p>BK Black Cord</p> <p>WH White Cord</p> <p>CB Clear Braided Cord</p> <p>*Dual aircraft cable + cord suspension.</p> <p>*Cable length field adjustable. Standard cord length 6ft. for longer cords, type desired length into product code above (i.e BK/8 = Black Cord + 8ft cord length).</p>	<p>SCONCE OPTIONS*</p> <p>ADA* ADA Compliant</p> <p>*See 'Dimensions & Mounting' on page 4 for ADA Sconce dimensions.</p> <p>*ADA compliant sconces are only available for remote driver location and standard shallow canopy.</p>	<p>WLNx (Cooper Wavelinx, remote)</p> <p>ENLGHt (Enlighted, remote)</p> <p>FCJS (Lutron, remote)</p> <p>FCJS/S (Lutron, remote, occ/daylight sensor)</p> <p>MLX (Molex POE, remote)</p> <p>NLT (nLight wired remote connection)</p> <p>NLTAIR (nLight AIR, remote connection, integral occ/daylight sensor)</p> <p>OS/PH/HV (Hubbel WASP remote occ/daylight sensor)</p> <p>*Default quantity is 1 sensor per fixture, type alternate quantity (/##) into product code above if desired and contact ALW to request price adjustment. Sensor descriptions available on page 10.</p> <p>*Not all sensors are compatible with all drivers. See 'Driver', 'Sensor' and lamping charts for driver details and sensor compatibility.</p>

*See page 6 for finish chart.

*Manually type the finish code into the parametric code above.

21. EMERGENCY OPTIONS* (OPTIONAL)

EMB⁷ Emergency Battery


*Emergency options only available with 0-10V driver options. Third party inverter system recommended for other driver options. Refer to [ALW EM Solution Catalog](#) for all compatibility exceptions.

⁷Available for deep canopy and remote mount only.




DIMENSIONS AND MOUNTING


CORE 3 PENDANT




CORE 3 SCONCE




REMOTE DRIVER STANDARD SHALLOW CANOPY




DEEP CANOPY MOUNTED DRIVER⁸ DEEP CANOPY FOR CANOPY MOUNTED DRIVERS



ADA COMPLIANT CORE 3 SCONCE ADA COMPLIANT




CUTOUT DIMENSIONS⁹ STANDARD DIMENSIONS FOR CUTOUT



BAFFLE Baffles are available for all cutout fixtures.

The baffle reflects light back into the fixture illuminating the heatsink and cutout features.



Not to scale. Dimensions are nominal. Consult factory for CAD drawings
All canopies fit standard 3.5" and 4" round and octagonal junction boxes.
⁸Deep canopy diameter depends on LED driver size
⁹Cutout position and dimension is consistent for all standard cutouts.



FINISHES

Standard finishes are available at no additional charge and no extended lead time for standard configurations.

STANDARD FINISHES



Brushed Aluminum



Aluminum Silver Anodized Effect



Satin White



Satin Black



Textured Black

PREMIUM FINISHES


BASIC POWDER COAT



Gloss White




Antimicrobial Gloss White




Textured Matte White

METALLIC POWDER COAT



Charcoal Gray



Copper



Brass

SATIN ANODIZED EFFECT POWDER COAT



Oil-Rubbed Bronze



Dark Bronze

GLOSS POWDER COAT (80-95% GLOSS)



Orange
RAL 2003



Red
RAL 3020



Magenta
RAL 4010



Blue
RAL 5015

Contact ALW Quotes for sample paint finish swatches.

SPECIAL ORDER FINISHES*



RAL CLASSIC COLORS (80-95% GLOSS): RAL_ _ _ _

Most RAL Classic Colors are available for a minimum setup fee. On your specification submittal choose your RAL color by entering the 4-digit RAL code (Ex: RAL 3003). See www.alw-inc.com/resources/finishes



CUSTOM COLOR MATCH: CCM_ _ _ _

Custom powder coat color matching is available for a premium setup fee. Consult ALW for additional information.

*An individual setup fee will apply to each unique Special Order Finish per purchase order. (ex: RAL 5023 and RAL 2008 are specified for multiple line items on a purchase order. 2x setup fees will apply)

*Printed or on-screen colors are only approximations - consult actual Color Chip Set before specifying

CORD OPTIONS



Black
Order Code = **BK**

For all locations



White
Order Code = **WH**

For all locations



Clear Silver Braid
Order Code = **CB**

For dry and damp locations only

SS121823



PERFORMANCE DETAILS

REFLECTOR OPTION	CRI	DELIVERED LUMENS ¹⁰	EFFICACY (LM/W)	WATTS(W)	CCT OPTIONS
15° 25° 35° 55° 80°	Ra = 90 ± 3	500	150	3.4	2700K 3000K 3500K 4000K
		1000	139	7.3	
		1500	132	11.5	
		2000	128	15.9	
		2500	124	20.4	
		3000	121	25.2	

*Based on 55deg reflector for all outputs, 4000K 90CRI.

*Refer to IES files for full performance data.

¹⁰Actual lumens measured in field may differ +/- 10%.

TM-30-18 DETAILS (90 CRI LAMPING)

CCT	CRI (Ra)	CRI (R9)	TM-30 Rf	TM-30 Rg
2700K	90.5	59.7	89.4	99.6
3000K	92.5	66.5	89.9	98.7
3500K	93.8	74.2	89.8	98.1
4000K	94.2	78.8	89.8	98.5




BIOS OVERVIEW



BIOS SkyBlue® technology is designed to provide the specific circadian stimulus required to improve overall sleep by **featuring a distinct peak in the 'skyblue' spectral power at 490nm**. Unlike traditional white LEDs, BIOS SkyBlue® makes it possible to achieve **high EML (Equivalent Melanopic Lux) and Melanopic/Photopic ratios** without harsh CCTs or high, glare-inducing light levels.

BIOS light engines are available for cylinder products with a **Dynamic** options for use with a variety of applications. Dynamic options include a dynamic board and Bio-Dimmer module to allow the user to dim-out the SkyBlue 490nm signal during night time hours.



BIOS DYNAMIC + BIO-DIMMING (BIOSD)	
DESCRIPTION	Dynamic light engine with Bio-Dimming add the ability to fine-tune and dim-out the 490nm SkyBlue signal during night time hours or as desired.
TYPICAL APPLICATIONS	Environments occupied for a 24-hour period such as hospitals, security facilities, behavioral health facilities, factories, etc.
CONTROLS & DIMMING	Works with any standard dimming controls (0-10V, Dali, EcoSystem, Triac, DMX, Wireless, etc.). BIOS SkyBlue® LED can be dimmed-out using a standard control/dimmer.

BIOS LED LAMPING DETAILS (DYNAMIC)

DELIVERED LUMENS ¹¹	WATTS (W)	EFFICACY (LM/W)
500	5.4	93
1000	11.1	90
1500	18.3	82
2000	23.8	77

BIOS LED PERFORMANCE DETAILS

CCT	CRI (R9) <i>Dynamic BIOS</i>	DAYTIME M/P RATIO ¹² <i>Dynamic BIOS</i>	NIGHTTIME M/P RATIO ¹² <i>Dynamic BIOS</i>	COI ¹³ <i>Dynamic BIOS</i>
3000K	83	0.73	0.45	3.3
3500K	83	0.84	0.50	3.1
4000K	83	0.95	0.55	3.1

¹¹Delivered Lumens calculations are based on LM-79 test of BIOS 4000K, 2000lm output.

¹²Melanopic to photopic (M/P) ratios are used to help calculate equivalent melanopic lux (EML) values which is the metric used for circadian lighting in the WELL™ Building Standard.


¹³BIOS SkyBlue® meets the Cyanosis Observation Index (COI) requirements for visual assessment of cyanosis, providing a COI up to 3.3.




BIOS DYNAMIC + BIO-DIMMING DIMMING CONTROL CHARACTERISTICS

	DIMMER SETTING	BIOS SKYBLUE® LED	WHITE LED	LIGHT OUTPUT		
	100%* (Full On)	100%	100%	100%	Bio-Dimming	BIOS SkyBlue® maintained for maximum circadian impact. Light output remains relatively constant.
	99% - 51%	100% - 0%	100%	100% - 90%		
	50%	NO BIOS	100%	~90%	White LED Intensity Dimming	BIOS SkyBlue® removed to provide minimal circadian impact. White LED output dims linearly.
	49% - 0%	NO BIOS	100% - 0%	Linear Dimming 90% - 0%		


Dynamic BIOS Lumen Output vs. Driver Current



BIOS + Bio-Dimming™



Dynamic BIOS SkyBlue vs. Driver Current





DRIVERS

PRODUCT CODE	DESCRIPTION
V00	0-10V dimming down to 0%
V01	0-10V dimming down to 1%
P01	Driver supports both TRIAC Forward Phase 2-Wire and ELV Reverse Phase 3-Wire dimming controls.
ELDVO	eldoLED, 0-10V dimming down to 0%
DALI	DALI flicker-free dimming down to 0%.
DMX	DMX flicker-free dimming down to 0%.
LDE1	ECOSYS1, (LDE1) Lutron Hi-Lume 1% EcoSystem LED driver with Soft-on, Fade-to-Black dimming technology
POEM	POE MOLEX. Molex CoreSync PoE LED Driver dimming down to 0.1%
POEI	IGOR PoE LED Driver. Contact ALW to assist with your project.
POEN	NuLEDS PoE LED Driver. Contact ALW to assist with your project.
POE	PoE Ready LED Driver. Contact ALW to assist with your project.

*Contact ALW for specific dimming level requests. ALW lighting fixtures are intended for use with a wide range of sensors, lighting controls, LED drivers, and building management systems. If there are specific components required for your application that aren't listed on this spec sheet, please contact ALW customer support today to specify a compatible solution of your choice.

DRIVER/LED LAMPING COMPATIBILITY				
	STD*	BIOS	CA TITLE 24 JA8/JA10 ¹⁴	IEEE P1789 & HD TV STUDIO ¹⁵
V00	●	●	●	
V01	●	●	●	
P01	●	●	●	
ELDVO	●	●	●	●
DALI	●	●	●	●
DMX	●	●	●	●
LDE1	●	●	●	●
POEM	PER REQUEST		●	●
POEI	PER REQUEST		●	●
POEN	PER REQUEST		●	●
POE	PER REQUEST		●	●

DRIVER LOCATION/DRIVER COMPATIBILITY			
	INTERNAL	DEEP CANOPY	REMOTE
V00		●	●
V01		●	●
P01		●	●
ELDVO		●	●
DALI		●	●
DMX		●	●
LDE1		●	●
POEM			●
POEI			●
POEN			●
POE			●

● - Indicates compatibility

*Standard lamping (STD) - 500-6000LM

¹⁴Fixtures specified with 90CRI 2700K, 3000K, 3500K, and 4000K lamping with applicable LED drivers have the ability to conform to California Title 24 JA8 and JA10 Appendices.

¹⁵The following drivers conform to IEEE P1789 Flicker Standard: 'IEEE Recommended Practices for Modulating Current in High-Brightness LEDs for Mitigating Health Risks to Viewers'. These drivers may also be installed in HD TV Studio applications utilizing high frequency camera equipment.

SS121823



SENSORS*

	PRODUCT CODE	DESCRIPTION	DRIVER LOCATION	SENSOR LOCATION
	N	None. Choose when sensors are not desired.	-	-
COOPER	WLNX	Fixture is built with 0/10V wiring to connect to Wavelinx Wireless sensors and power/relay packs (sensors and equipment not provided by ALW)	Internal Deep Canopy Remote	Remote
ENLIGHTED™	ENLGHT	Enlighted® remote connected lighting smart sensor - occ/daylight/networking (Enlighted Part: SU-5S-H-CL)	Remote	
LUTRON VIVE	FCJS	Lutron® Vive remote RF wireless fixture control (Lutron Part: FCJS-ECO or FCJS-010)	Remote	
	FCJS/S	Lutron® Vive remote RF wireless fixture control + daylight/occ sensor (Lutron Part: FCJS-ECO or FCJS-010, & FC-Sensor)	Remote	
MOLEX POE CORESYNC	MLX	Molex PoE sensors for use with Molex/PoE drivers. Customer will need to determine who to purchase PoE equipment from.	Remote	
NLIGHT WIRED®	NLT	Fixture is built to connect to nLight Wired remote components specified by agency. Contact ALW to review project details.	Remote	
NLIGHT WIRELESS®	NLTAIR	Fixture is built to connect to nLight Air (Wireless) remote components specified by agency. Contact ALW to review project details.	Remote	
VALUE SENSORS	OS/PH/HV	<i>Hubbell WASP High Voltage 0-10V remote surface mount occ/daylight sensor. 120/277/347VAC input (Hubbell Part: WSPDSMUNV) Automated Dimming Functionality: Connect fixture 0/10V wires to sensor in the field. Adjust occ/photocell settings as desired. On/Off or Manual Dimming Functionality: Turn photocell functionality OFF. Cap off 0/10V wires on sensor. Connect fixture 0/10V wires to wall dimmer in the field.</i>	Internal Deep Canopy Remote	

*All connected lighting sensors/systems must be programmed in the field by an electrical commissioner familiar with the system. Refer to the 'Sensor Compatibility' and 'Driver/Sensor Compatibility' charts to specify compatible sensors, LED lamping, and LED driver systems.

SENSOR COMPATIBILITY					
PRODUCT CODE		SENSOR TYPE	MAX MT HT	CA TITLE 24	STD*
COOPER WAVELINX	WLNX		15 ft	●	●
ENLIGHTED™	ENLGHT	OCCUPANCY/PHOTOCELL	40 ft	●	●
LUTRON VIVE	FCJS	WIRELESS CONTROL	12 ft	●	●
	FCJS/S	OCCUPANCY/PHOTOCELL	12 ft	●	●
MOLEX POE CORESYNC	MLX		16 ft	●	●
NLIGHT WIRED	NLT		15 ft	●	●
NLIGHT WIRELESS	NLTAIR		15 ft (average)	●	●
VALUE SENSORS	OS/PH/HV	OCCUPANCY/PHOTOCELL	45 ft	●	●

● - Indicates compatibility ■ - On/off sensor functionality only

*Standard lamping (STD) - 500 - 6000LM

DRIVER/SENSOR COMPATIBILITY									
	WLNX	ENLGHT	MLX	FCJS	FCJS/S	NLT	NLTAIR	OS/PH/HV	NO SENSOR
V00	●	●		●	●			■	●
V01	●	●		●	●			■	●
P01								■	●
ELDVO						●	●	▲	●
DALI								■	●
DMX								■	●
LDE1				●	●				●
POEM			●						●
POEI	Sensor types will depend on the PoE system configuration. Contact ALW for details.								
POEN	Sensor types will depend on the PoE system configuration. Contact ALW for details.								
POE	Sensor types will depend on the PoE system configuration. Contact ALW for details.								

● - Indicates compatibility

▲ - Fixture can have automated dimming via sensor OR on/off functionality and manual dimming

■ - On/off sensor functionality only



PHOTOMETRICS CORE 3

BEAM ANGLE (°)	POLAR PLOT (CD)	MTG HEIGHT (FT)	LIGHT LEVEL (FC)	BEAM DIAMETER (FT)	SPACING CRITERION (SC) ¹⁶ (0° - 180°) (90° - 270°)	MAX INTENSITY (CD)
15°		6	446.8	1.8	.30 .30	16086
		8	251.3	2.5		
		10	160.9	3.1		
		12	117.7	3.7		
		14	82.1	4.3		
		16	62.8	4.9		
25°		6	262.3	2.6	.39 .39	9443
		8	147.6	3.4		
		10	94.4	4.3		
		12	65.6	5.1		
		14	48.2	6.0		
		16	36.9	6.8		
35°		6	205.1	3.7	.55 .55	7383
		8	115.4	4.9		
		10	73.8	6.2		
		12	51.3	7.4		
		14	37.7	8.7		
		16	28.8	9.9		
55°		6	117.4	6.2	.85 .85	4227
		8	66.1	8.2		
		10	42.3	10.3		
		12	29.4	12.3		
		14	21.6	14.4		
		16	16.5	16.4		
80°		6	54.3	10.1	1.36 1.36	2103
		8	30.5	13.4		
		10	19.5	16.8		
		12	13.6	20.1		
		14	10.0	23.5		
		16	7.6	26.8		

*Photometric calculations based on 3000lm 4000K 90 CRI fixture combination. Actual results may vary in the field.

For footcandle and output multipliers refer to the [ALW IES File Multipliers Chart](#).

¹⁶Spacing criterion refers to maximum distance luminaires can be spaced to provide uniform illumination on the working plane or surface.

Luminaire spacing = Spacing Criterion (SC) x Mounting Height (MH) (ex. 1.14 (SC) x 10' (MH) = 11.4' Luminaire Spacing).



ADDITIONAL OPTIONS & SPECIFICATIONS

LED PERFORMANCE

> 55,000 hours at 80% lumen maintenance, LM80 / TM-21

COLOR CONSISTENCY

3 SDCM; 90 CRI typical

HOUSING

Extruded aluminum with galvanized steel hardware

SAFETY & REGULATORY

Can be used to comply with **Title 24 JA8 and JA10** requirements. Contact ALW customer support today and we can help you with your project requirements.

UL Listed (U.S. & Canada). Suitable for dry or damp locations. Conforms to UL 2108, 8750
Certified to CSA std. CSA C22.2# 9 & #250.0

OPERATING TEMPERATURE

Luminaire should be installed and operated **ONLY** in dry or damp environments where the ambient temperature ranges from -4 °F to 104 °F (-20 °C to 40 °C). Luminaire operation in environments outside the listed temperature range voids the warranty AND may damage the product or adversely impact lamp life, lumen output and color consistency.

CONTROLS, SENSORS, & LED DRIVER

ALW lighting fixtures are intended for use with a wide range of sensors, lighting controls, LED drivers, and building management systems. Our component portfolio is continually expanding to adopt to the latest technologies and specification needs. We currently support integration with Lutron, Enlighted, EldoLED, nLight, Osram, Philips, and more. If there's a component or system needed that you don't see on the spec sheet please contact ALW customer support today so we can review your requirements.

WARRANTY

LIMITED WARRANTY. Visit alw-inc.com for more information.

WEIGHT

CORE 3	
PENDANT	SCONCE
4.5 lbs/ 2.1 kg	2.5 lbs/ 1.1 kg